

Amendments to the Claims:

Please AMEND claims 1, 4, 11, 12, 16, and 18 and cancel claim 8. A copy of all pending claims and a status of the claims are provided below. This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A plasma display panel comprising a fluorescent layer that includes a red phosphor pattern, a green phosphor pattern, and a blue phosphor pattern, the red phosphor pattern containing $\text{Y(V,P)O}_4\text{:Eu}$ and $(\text{Y,Gd})\text{BO}_3\text{:Eu}$ and having a red-color purity ranging from 0.657 to 0.670 for a chromaticity coordinate value x and from 0.322 to 0.332 for a chromaticity coordinate value y.

2. (original) The plasma display panel of claim 1, wherein the amount of $\text{Y(V,P)O}_4\text{:Eu}$ is in the range of 20-80% by weight based on the total weight of $\text{Y(V,P)O}_4\text{:Eu}$ and $(\text{Y,Gd})\text{BO}_3\text{:Eu}$.

3. (original) The plasma display panel of claim 1, wherein the amount of $\text{Y(V,P)O}_4\text{:Eu}$ is in the range of 50-80% by weight based on the total weight of $\text{Y(V,P)O}_4\text{:Eu}$ and $(\text{Y,Gd})\text{BO}_3\text{:Eu}$.

4. (Currently Amended) A plasma display panel comprising a fluorescent layer that includes a red phosphor pattern, a green phosphor pattern, and a blue phosphor pattern, wherein the plasma display panel is without a color-compensating filer, ~~and the~~

red phosphor pattern contains $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$, and the red light has an afterglow decay time of 4.0-8.8 ms.

5. (original) The plasma display panel of claim 4, wherein the amount of $Y(V,P)O_4:Eu$ is in the range of 20-80% by weight based on the total weight of $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

6. (original) The plasma display panel of claim 4, wherein the amount of $Y(V,P)O_4:Eu$ is in the range of 50-80% by weight based on the total weight of $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

7. (original) The plasma display panel of claim 4, having a red-color purity ranging from 0.657 to 0.670 for a chromaticity coordinate value x and from 0.322 to 0.332 for a chromaticity coordinate value y.

8. (cancelled)

9. (original) The plasma display panel of claim 4, having a red-color purity ranging from 0.660 to 0.670 for a chromaticity coordinate value x and from 0.322 to 0.330 for a chromaticity coordinate value y.

10. (original) The plasma display panel of claim 4, having an afterglow decay time of 4.0-8.0 ms for red light.

11. (Currently Amended) A plasma display panel comprising a fluorescent layer that includes a red phosphor pattern, a green phosphor pattern, and a blue phosphor pattern, wherein the plasma display panel is not provided with a color-compensation filter, and the red phosphor pattern includes two phosphors with ~~and has a combined~~ red-color purity ranging from 0.657 to 0.670 for a chromaticity coordinate value x and from 0.322 to 0.332 for a chromaticity coordinate value y.

12. (Currently Amended) A plasma display panel comprising a fluorescent layer that includes a red phosphor pattern ~~phosphor pattern~~, a green phosphor pattern, and a blue phosphor pattern, wherein the plasma display panel is without a color-compensation filter and has an afterglow decay time of 4.0-8.8 ms for red light.

13. (original) The plasma display panel of claim 11, wherein the red phosphor pattern contains $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

14. (original) The plasma display panel of claim 12, wherein the red phosphor pattern contains $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

15. (original) The plasma display panel of claim 13, wherein the amount of $Y(V,P)O_4:Eu$ is in the range of 20-80% by weight based on the total weight of $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

16. (Currently Amended) A plasma display panel comprising a fluorescent layer that includes a red phosphor pattern, a green phosphor pattern, and a blue phosphor

pattern, wherein the plasma display panel is without a color-compensation filter, and
the red phosphor pattern includes two phosphors with a combined ~~and has a red-color~~
purity ranging from 0.660 to 0.670 for a chromaticity coordinate value x and from 0.322
to 0.332 for a chromaticity coordinate value y.

17. (original) A plasma display panel comprising a fluorescent layer that includes
a red phosphor pattern, a green phosphor pattern, and a blue phosphor pattern,
wherein the plasma display panel is without a color-compensation filter and has an
afterglow decay time of 4.0-8.0 ms for red light.

18. (Currently Amended) The plasma display panel of claim ~~15~~17, wherein the
red phosphor pattern contains $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

19. (original) The plasma display panel of claim 16, wherein the red phosphor
pattern contains $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.

20. (original) The plasma display panel of claim 13, wherein the amount of
 $Y(V,P)O_4:Eu$ is in the range of 50-80% by weight based on the total weight of
 $Y(V,P)O_4:Eu$ and $(Y,Gd)BO_3:Eu$.